

MATERIAL SAFETY DATA SHEET

LONE STAR LUBRICANTS
2232 MONEDA ST.
FORT WORTH, TX 76117-5310
(817) 831-2522 Fax (817) 834-0447

SECTION 1

IDENTITY (AS USED ON LABEL): LS-28 (CP-28)
CHEMICAL NAMES AND SYNONYMS: Grease, Assembly Lube
CHEMICAL FAMILY: Not applicable
FORMULA: Complex mixture
DATE PREPARED: March 15, 2010
INFORMATION OR EMERGENCY PHONE: (817) 831-2522
PREPARED BY: CHEMICAL COMMUNICATIONS COORDINATOR
LONE STAR LUBRICANTS, 2232 Moneda St. Ft. Worth, TX 76117

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS)

HEALTH: 1
FLAMMABILITY: 1
REACTIVITY: 0
SPECIAL NOTICE: -

SECTION 2 - HAZARDOUS COMPONENTS

CONCENTRATIONS

Molybdenum Disulfide (CAS #1317-33-5)

ACGIH TLV: 10 mg/m³ as Mo

OSHA PEL: 10 mg/m³ as Mo

Trade Secret

Lithium Grease:

ACGIH TLV: No Listing

OSHA PEL: No Listing

Trade Secret

*This chemical is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40CFR Part 372.

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Not applicable
Density (lb/gal): 15.0
Vapor Pressure (m Hg.): Not available
Melting Point: Not available
Vapor Density (AIR=1): Not available
Evaporation Rate: Not available
(Butyl Acetate = 1)
Solubility in Water: Nil
Appearance and Odor: Gray/black grease, no odor
Volatile Organic Compound -
Voc (grams/liter): Not applicable

SECTION 4 - FIRE AND EXPLOSIVE HAZARD DATA

Flash Point (Method Used): >300°F (C.O.C.)

Flammable Limits:

LEL - Not determined for product

UEL- Not determined for product

Extinguishing Media: CO2, Foam, Dry Chemical or Halon

Special Fire Fighting Procedures:

Wear self-contained breathing apparatus. Do not extinguish with water.

Unusual Fire and Explosion Hazards:

Irritating and /or toxic fumes, including oxides of sulfur and carbon may be released in a fire situation.

SECTION 5 - REACTIVITY DATA

Stability: Stable

Conditions to Avoid: Open flame

Incompatibility (Materials to Avoid):

Strong oxidizing agents

Hazardous Decomposition Products:

Irritating and/or toxic fumes including Barium, Sulfur, Carbon and Amine Compounds may be released.

Hazardous Polymerization: Will not occur

Conditions to Avoid: None

SECTION 6 - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Not determined for product, see Section II.

Route(s) of Entry:

Inhalation? No

Skin? Yes

Ingestion? Yes

TOXICITY (ACUTE AND CHRONIC):

Synthetic oils may cause skin and eye irritation.

CARCINOGENICITY: NTP-NO IARC-NO OSHA-NO

Molybdenum compounds may be slightly irritating.

CARCINOGENICITY: NTP-NO IARC-NO OSHA-NO

HEALTH HAZARDS:

Eyes - can cause irritation , redness, blurred vision.

Skin - prolonged contact can cause irritation and dermatitis.

Ingestion - can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

EMERGENCY AND FIRST AID:

Skin - wash with soap and water.

Eyes - flush with copious amounts of water, get medical attention.

Ingestion - do not induce vomiting, keep warm, get medical attention.

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE**Steps To Be Taken in Case Material is Released for Spilled:**

Clean spill with absorbent material

Eliminate ignition sources

Do not store oily materials in enclosed containers for long periods of time

Wear gloves, goggles and gas mask if TWA's are exceeded.

Waste Disposal Methods:

Dispose of waste in a chemical landfill as approved by current local, state and federal laws and regulations.

Precautions to be Taken in Handling and Storing:

Protect from physical damage. Store in a cool, dry, ventilated area away from acids, alkalis, and open flames.

Other Precautions:

None

SECTION 8 - CONTROL MEASURES**Respiratory Protection:**

Use NIOSH approved organic respirator if TWA/TLV limits are exceeded.

Ventilation:

Local Exhaust -

Use to maintain levels below TWA limits.

Mechanical -

Use non sparking equipment.

Special:

None

Other:

None

Protective Gloves:

Chemical resistant gloves

Eye Protection:

Wear safety glasses or goggles

Other Protective Equipment or Practices:

None

SECTION 9: - PHYSICAL/CHEMICAL CHARACTERISTICS**Boiling Point:**

Not applicable

Density (lb/gal):

15.0

Vapor Pressure (m Hg.):

Not available

Melting Point:

Not available

Vapor Density (AIR=1):

Not available

Evaporation Rate:

Not available

(Butyl Acetate = 1)

Solubility in Water:

Nil

Appearance and Odor:

Gray/black grease, no odor

Volatile Organic Compound -

Voc (grams/liter):

Not applicable

SECTION 13: DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use.

Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent material and residues at the time of disposition.

Conditions of use may cause this material to become a “hazardous waste”, as defined by federal or state regulations. It is the responsibility of the user to determine if the material is a “hazardous waste” at the time of disposal. Transportation, treatment, storage, and disposal of waste material must be conducted in accordance with RCRA regulations (see 40 CFR 260 through 40 CFR 271). State and/or local regulations may be more restrictive. Contact your regional US EPA office for guidance concerning case specific disposal issues. Empty drums and pails retain residue. DO NOT pressurize, cut, weld, braze solder, drill or expose this products empty container to heat, flame or other ignition sources. DO NOT attempt to clean it. Empty drums and pails should be drained completely, properly bunged or sealed, and promptly sent to a reconditioner.

SECTION 14: TRANSPORTATION INFORMATION

The shipping description below may not represent requirements for all modes of transportation, shipping methods or locations outside of the United States.

US DOT Status	Not regulated by the U.S. Department of Transportation as a hazardous material.
Proper Shipping Name	Not regulated
Hazard Class	Not regulated
Reportable Quantity	3,500 lbs
Other Requirements	Not applicable

SECTION 15: REGULATORY INFORMATION

The components of this product are listed on the EPA/TSCA inventory of chemical substances.

Protection of stratospheric ozone (pursuant to SECTION 611 of the Clean Air Act Amendments of 1990):

Per 40 CFR part 82, this product does not contain nor was in directly manufactured with any Class I or Class II ozone depleting substances.

In accordance with SARA title III, Section 313, The attached Environmental Data Sheet (EDS) should always Be copied and sent with the MSDS.

SECTION 16: STATE REGULATORY INFORMATION

California Proposition 65: This material should not contain any of the components which are known to the State of California to cause cancer or birth defects or other reproductive harm Subject to the CA= California Hazardous Substance List; CA65C, CA65R, CA65C/R = California Safe Drinking Water and Toxics Enforcement Act of 1986 or Proposition 65 List.

New Jersey

Petroleum Oil

Additional Remarks

No components listed: CT=Connecticut Toxic Substance List, IL, LA, MA, NJ, NY, FL, PA, RI or as defined under Hazardous Substance for: CA, IL, LA, FL, NJ, PA.
More State information to be added as received

EMERGENCY OVERVIEWHazard Rankings

		HMIS	NFPA
Physical State: Semi-Solid to Solid (Smooth texture)	Health Hazard	0	0
Color: Black	Fire Hazard	1	1
Odor: Mild petroleum odor	Reactivity	0	0

WARNING:

INJECTION UNDER SKIN CAN CAUSE SEVERE INJURY.

Most damage occurs in the first few hours.

Initial symptoms may be minimal.

Hot grease will cause thermal burns upon contact.

Protective Equipment

Spills may create a slipping hazard.

DISCLAIMER OF LIABILITY

THE INFORMATION IN THIS MSDS WAS OBTAINED FROM SOURCES WHICH WE BELIEVE ARE RELIABLE. HOWEVER, THE INFORMATION IS PROVIDED WITHOUT ANY WARRANTY, EXPRESSED OR IMPLIED REGARDING ITS CORRECTNESS. SOME INFORMATION PRESENTED AND CONCLUSIONS DRAWN HEREIN ARE FROM SOURCES OTHER THAN DIRECT TEST DATA ON THE SUBSTANCE ITSELF. THIS MSDS WAS PREPARED AND IS TO BE USED ONLY FOR THIS PRODUCT. IF THE PRODUCT IS USED AS A COMPONENT IN ANOTHER PRODUCT, THIS MSDS INFORMATION MAY NOT BE APPLICABLE. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE.

THE CONDITIONS OR METHODS OF HANDLING, STORAGE, USE, AND DISPOSAL OF THE PRODUCT ARE BEYOND OUR CONTROL AND MAY BE BEYOND OUR KNOWLEDGE. FOR THIS AND OTHER REASONS, WE DO NOT ASSUME RESPONSIBILITY AND EXPRESSLY DISCLAIM LIABILITY FOR LOSS, DAMAGE OR EXPENSE ARISING OUT OF OR IN ANY WAY CONNECTED WITH HANDLING, STORAGE, USE OR DISPOSAL OF THE PRODUCT.

END OF MSDS

INFORMATION ON THIS FORM IS FURNISHED SOLELY FOR THE PURPOSE OF COMPLIANCE WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29CFR 1910.1200 AND SHALL NOT BE BE USED FOR ANY OTHER PURPOSE.

(SIMILAR TO OSHA FORM 174)